

TYPE OF CONTAINER	GENERAL USE	SIZE	WEIGHT *			INTERNAL DIMENSIONS*			DOOR OPENINGS*		VOL.		Notes	
			Kilograms		Lbs	millimeters		feet/inches		millimeters	feet/inches	m <sup>3</sup>		ft. <sup>3</sup>
			Feet	Max. Gross Wt.	Tare Wt.	Max. Payload	Length	Width	Height	Width	Height	Capacity		
<b>Dry Van/General</b>	Suitable for commodities in bundles, cartons, boxes, loose cargo, furnitures, etc.	20	24,000	2,200	21,800	5,902	2,350	2,392	2,341	2,280	33.2	All steel construction		
			52,910	4,850	48,060	19' 4 23/64"	7' 8 33/64"	7' 10 11/64"	7' 8 11/64"	7' 5 49/64"	1,172			
<b>High Cube</b>	Same as dry containers, but higher volume capacity	40	30,480	3,800	26,680	12,032	2,350	2,390	2,338	2,280	67.6	Steel		
			67,200	8,380	58,820	39' 5 45/64"	7' 8 33/64"	7' 10 7/64"	7' 8 3/64"	7' 5 49/64"	2,387			
<b>Open Top</b>	Suitable for high large piece cargo that cannot be loaded through container doors such as machinery, sheet glass, marble, building materials and lumber.	20	24,000	2,140	21,860	5,894	2,344	2,347	2,336	2,275	31.5	Steel		
			52,910	4,717	48,192	19' 4 1/8"	7' 8 5/16"	7' 8 3/8"	7' 7 15/16"	7' 5 1/2"	1,112			
<b>Bulk</b>	Designed for the carriage of all dry free flowing materials such as chemicals, powders and granules, cement fertilizers, flour, milk powder, sugar, salt and granular plastic products.	40	30,480	3,700	26,780	12,027	2,344	2,347	2,336	2,275	67.0	Steel		
			67,200	8,158	59,049	39' 5 1/2"	7' 8 5/16"	7' 8 3/8"	7' 7 15/16"	7' 5 1/2"	2,365.6			
<b>Flat Platform Collapsible Flush Folding</b>	Used for carrying awkward and oversize loads such as machinery, cables, drums, sheet and steel coils, heavy vehicles, timber and forest products	20	25,400	3,080	22,320	5,988	2,398	2,231				Steel		
			56,000	6,790	49,210	19' 7 3/4"	7' 10 3/8"	7' 7 3/8"						
<b>Open Side</b>	Suitable for cargo that consists of large pieces that can not be loaded through container doors. Convenient for loading/unloading at railway sidings	40	45,000	5,300	39,700	12,064	2,369	1,943				Steel		
			99,202	11,683	87,518	11,662	2,179							
<b>Reefer</b>	Suitable for transporting perishable cargo such as vegetables, fruit, meat, etc.	20	25,400	2,870	22,530	5,460	2,240	2,225	2,240	2,180	31.0	Aluminum		
			56,000	6,330	49,670	17' 10 3/4"	88 1/16"	87 1/2"	88 1/8"	85 5/8"	1094.5			
<b>ISO Tank</b>	<b>IMO1:</b> Suitable for hazardous substances such as toxic, corrosive, highly flameable liquids. <b>Non-hazardous tanks:</b> Suitable for oils, plasticisers, resins, natural or synthetic latex, milk, still beers, wine, mineral water.	40	32,500	4,535	27,965	11,550	2,250	2,215	2,250	2,160		Aluminum & Stainless Steel		
			71,650	9,998	61,652	37' 10 1/2"	88 1/2"	87 1/2"	88 1/2"	85"				
<b>ISO Tank</b>	<b>IMO1:</b> Suitable for hazardous substances such as toxic, corrosive, highly flameable liquids. <b>Non-hazardous tanks:</b> Suitable for oils, plasticisers, resins, natural or synthetic latex, milk, still beers, wine, mineral water.	20	30,480	3,070	27,410						21,000	Stainless Steel		
			67,200	6,768	60,425						5,547 US gallons			

All drawings shown are 20' containers

\* The dimensions and weights are based on plant manufacturers' specifications. Tolerance factors must always be taken into account by the shipper