

TYPE OF CONTAINER	GENERAL USE	SIZE	WEIGHT *			INTERNAL DIMENSIONS*			DOOR OPENINGS*		VOL.		Notes	
			Kilograms		Lbs	millimeters		feet/inches		millimeters	feet/inches	m ³		ft. ³
			Feet	Max. Gross Wt.	Tare Wt.	Max. Payload	Length	Width	Height	Width	Height	Capacity		
Dry Van/General	Suitable for commodities in bundles, cartons, boxes, loose cargo, furnitures, etc.	20	24,000 52,910	2,200 4,850	21,800 48,060	5,902 19' 4 23/64"	2,350 7' 8 33/64"	2,392 7' 10 11/64"	2,341 7' 8 11/64"	2,280 7' 5 49/64"	33.2 1,172	All steel construction		
		40	30,480 67,200	3,800 8,380	26,680 58,820	12,032 39' 5 45/64"	2,350 7' 8 33/64"	2,390 7' 10 7/64"	2,338 7' 8 3/64"	2,280 7' 5 49/64"	67.6 2,387			
High Cube	Same as dry containers, but higher volume capacity	40	30,480 67,200	3,900 8,600	26,580 58,600	12,033 39' 5 47/64"	2,350 7' 8 33/64"	2,695.5 8' 10 1/8"	2,338 7' 8 3/64"	2,585 8' 5 49/64"	76.2 2,690	Steel		
Open Top	Suitable for high large piece cargo that cannot be loaded through container doors such as machinery, sheet glass, marble, building materials and lumber.	20	24,000 52,910	2,140 4,717	21,860 48,192	5,894 19' 4 1/8"	2,344 7' 8 5/16"	2,347 7' 8 3/8"	2,336 7' 7 15/16"	2,275 7' 5 1/2"	31.5 1,112	Steel		
		40	30,480 67,200	3,700 8,158	26,780 59,049	12,027 39' 5 1/2"	2,344 7' 8 5/16"	2,347 7' 8 3/8"	2,336 7' 7 15/16"	2,275 7' 5 1/2"	67.0 2,365.6			
Bulk	Designed for the carriage of all dry free flowing materials such as chemicals, powders and granules, cement fertilizers, flour, milk powder, sugar, salt and granular plastic products.	20	24,000 52,910	2,800 6,180	21,200 46,340	5,888 19' 4"	2,332 7' 8"	2,338 7' 9"	2,340 7' 8"	2,263 7' 5"	32.4 1,144	Steel and fiberglass coated		
Flat Platform Collapsible Flush Folding	Used for carrying awkward and oversize loads such as machinery, cables, drums, sheet and steel coils, heavy vehicles, timber and forest products	20	25,400 56,000	3,080 6,790	22,320 49,210	5,988 19' 7 3/4"	2,398 7' 10 3/8"	2,231 7' 7 3/8"				Steel		
		40	45,000 99,202	5,300 11,683	39,700 87,518	12,064 11,662 (between posts)	2,369 2,179 (between stanchions)	1,943 (loading height)						
Open Side	Suitable for cargo that consists of large pieces that can not be loaded through container doors. Convenient for loading/unloading at railway sidings	20	25,400 56,000	2,930 6,460	22,470 49,540	5,896 19' 4 1/8"	2,310 7' 6 15/16"	2,255 7' 4 49/64"	2,236 7' 8 3/64"	1,960 6' 5 5/32"	31.0 1094.5	Steel		
Reefer	Suitable for transporting perishable cargo such as vegetables, fruit, meat, etc.	20	25,400 56,000	2,870 6,330 (without generator)	22,530 49,670 (without generator)	5,460 17' 10 3/4"	2,240 88 1/16"	2,225 87 1/2"	2,240 88 1/8"	2,180 85 5/8"		Aluminum		
		40	32,500 71,650	4,535 9,998	27,965 61,652	11,550 37' 10 1/2"	2,250 88 1/2"	2,215 87 1/2"	2,250 88 1/2"	2,160 85"		Aluminum & Stainless Steel		
ISO Tank	IMO1: Suitable for hazardous substances such as toxic, corrosive, highly flameable liquids. Non-hazardous tanks: Suitable for oils, plasticisers, resins, natural or synthetic latex, milk, still beers, wine, mineral water.	20	30,480 67,200	3,070 6,768	27,410 60,425						21,000 Liters 5,547 US gallons	Stainless Steel		

All drawings shown are 20' containers

* The dimensions and weights are based on plant manufacturers' specifications. Tolerance factors must always be taken into account by the shipper